





MIRA LED



Characteristic

Ingress protection of optical system and driver	IP 66
Electrical class	II
Nominal input voltage	120 - 277 V AC
Frequency	50/60 Hz
Operating temperatures	-40°C to +55°C
Material	anodized aluminium alloy
Colour	inox / graphite
Setup	pole top mounted Ø60x80; recommended mount height 4 to 5 m,
Optical system	ROSA PMMA lens
LEDs type	CREE XM-L2
LEDs lifetime L90	>50 000h
Warranty	5 years





Technical parameters

Type	MIRA LED 36	
Code	214532/6	214532/3
Correlated colour temperature [K]	5 000	3 500
Color rendering index CRI	75 ²⁾	>80
LEDs quantity	12	
Supply current [mA]	1 000	
LEDs power [W]	36	
LEDs luminous flux ¹⁾ [lm]	5 250	4 300
Power consumption [W]	42	
Luminaire luminous flux ¹⁾ [lm]	4 900	4 000
Luminaire efficacy [lm/W]	117	95
Weight [kg]	6,1	
Volume [m³]	0,115	
Windage [m²]	0,029	

- 1)

including LEDs tolerance parameter accuracy +/- 3%
- 2)

parameter accuracy +/-2
- Low voltage directive LVD 2006/95/WE, norm PN-EN 60598-1, PN-EN 60598-2-3
- Directive EMC 2004/108/WE, norms: PN-EN 55015, PN-EN 61547, PN-EN 61000-3-2, PN-EN 61000-3-3
- Shown parameters based on measurements according to IESNA LM 79-08

Distribution of MIRA LED

